



G2H07



Series		G2H07*****
Design		Turbine
Housing		Stainless Steel
Fitting Size	Option 1	3/4 inch
Fitting Type	Option 1	NPT
	Option 2	ISO
Flow Range	GPM	2-20 GPM
	LPM	7.6-75.7 LPM
Accuracy		+ -1.5% of reading
Repeatability		+ -.1%
Pressure Rating	PSIG	3000 PSIG
	bar	207 bar
Operating Temperature Range	Fahrenheit	14 to 140°F
	Celsius	-10 to 60°C
Typical K Factor		1110
Wetted Components	Housing	316 SS
	Journal Bearings	Ceramic
	Shaft	Tungsten Carbide
	Rotor	PVDF (Kynar)
	Rings	316 SS
Frequency Range		37-370 Hz @ 2-20 GPM
Strainer Size		55 mesh
Maximum Flow	GPM	30 GPM
	LPM	113.6 LPM
Maximum Pressure Drop in 10:1 Range	PSIG	7.5 PSIG
	bar	0.5 bar
Wrench Flat Size	Inch	5/16 inch
	mm	41 mm
Weight - Turbine Only	lbs	2 lbs
	kg	1 kg
Weight - Turbine with Computer	lbs	2.3 lbs
	kg	1.1 kg
Shipping Weight - Turbine Only	lbs	2.2 lbs
	kg	1 kg
Shipping Weight - Turbine with Computer	lbs	2.4 lbs
	kg	1.1 kg
Electronic Features	Feature 1	2 Totals(1 Resettable/1 Cumulative)
	Feature 2	Factory Cal in Gal or Litre
	Feature 3	2 User Calibrations and Flowrate