Unit 7 Swan Business Centre, Buckingham, MK18 1TB
01280 817304
01280 817185
sales@bellflowsystems.co.uk

CGI-50 230 V

Centrifugal self-priming pump

TECHNICAL CARD

code. 02170

222a

52 l/min

230 VAC





USE

- Centrifugal self-priming pump with JET-venturi system with high suction capacity for AdBlue/DEF even with small amounts of air-gas in the water.
- It is suitable for home applications, pressure groups, garden watering, washing, etc.
- Compact and noiseless pump with high suction power
- For suctions higher than 4 m, it is advisable to install a suction pipe higher than 1".

OPERATION

Fluid: clean water, AdBlue/DEF
Minimum/maximum liquid Temperature: -5 ºC / +40 ºC
Maximum working pressure: 3 bar
Maximum suction height: 8 m

TECHNICAL FEATURES

- Flow: 22-52 l/min
- Maximum pressure: 3 bar
- Motor: 0.37 kW 230 VAC 50 Hz · single-phase · self-ventilated
- IP-44 protection
- 2,800 rpm
- Consumption: 2.1 A
- LeqA(dB):72
- Inlet/Outlet connection: 1" GAS BSP
- ON/OFF Switch
- 2 m electrical cable with approved plug