



Hose reel Z



DIESEL



FEATURES

	DIESEL <i>without hose</i>	DIESEL <i>with hose</i>	Ad Blue® <i>without hose</i>	Ad Blue® <i>with hose</i>
Inlet ["]:	3/4"M	3/4"M	3/4"M	3/4"M
Outlet * ["]:	1/2"F	3/4"M; 1" M	1/2"F	3/4"M; 1" M
Max pressure [bar]:	10	10	10	10
Max hose Ø [mm]:	20	20	20	20
Max hose length [m]:	8	8	8	8
Included hose (length; Ø) [m; mm]:	-	8; 20	-	8; 20
Flow losses [lpm]:	5 @ 60lpm	5 @ 60lpm	5 @ 60lpm	5 @ 60lpm
Protection cover:	included	included	included	included
Hose's auto-stop system:	yes	yes	yes	yes
Allowed fluids:	Diesel	Diesel	Ad Blue®, AUS 32	Ad Blue®, AUS 32
Forbidden fluids:	gas, alcool, water, gasoline, kerosene	gas, alcool, water, gasoline, kerosene	gas, alcool, diesel gasoline, kerosene	gas, alcool, diesel gasoline, kerosene
Material:	painted steel, ABS	painted steel, ABS	painted steel, ABS	painted steel, ABS
Sealing material:	Viton, Teflon	Viton, Teflon	Viton, Teflon	Viton, Teflon
Fitting material:	steel	steel	stainless steel	stainless steel
Temperature min; max [°C]:	-20/+55	-20/+55	-20/+55	-20/+55
Dimension [mm]:	510x280x550	510x280x550	510x280x550	510x280x550
Weight (without hose) [Kg]:	11.5	11.5	11.5	11.5
Weight (with hose) [Kg]:	-	14.9	-	14.5

Accessories:

Fittings
Adjustable wall support

* refers to hose outlet in models with hose



Hose reel P



DIESEL



FEATURES

	DIESEL <i>without hose</i>	DIESEL <i>with hose Ø20</i>	DIESEL <i>with hose Ø25</i>
Inlet ["]:	1"F	1"F	1"F
Outlet * ["]:	1" M	1" M; 3/4"M	1" M
Max pressure [bar]:	10	10	10
Max hose Ø [mm]:	25; 20	20	25
Hose fitting:	Ø 25 M; Ø 20 M	Ø 20 M	Ø 25 M
Max hose length [m]:	10; 15	10; 15	10
Included hose (length) [m]:	-	10 - 15	10
Flow losses [lpm]:	4 @ 70lpm	4 @ 70lpm	4 @ 70lpm
Protection cover:	-	included	included
Hose's auto-stop system:	yes	yes	yes
Allowed fluids:	Diesel	Diesel	Diesel
Forbidden fluids:	gas, alcool, water, gasoline, kerosene	gas, alcool, water, gasoline, kerosene	gas, alcool, water, gasoline, kerosene
Material:	painted steel	painted steel	painted steel
Sealing material:	NBR	NBR	NBR
Fitting material:	nichel plated steel, brass	nichel plated steel, brass	nichel plated steel, brass
Temperature min; max [°C]:	-20/+55	-20/+55	-20/+55
Dimension [mm]:	640x310x700	640x310x700	640x310x700
Weight (without hose) [Kg]:	25	25	25
Weight (with hose) [Kg]:	-	29.3; 31	32

Accessories:

Fittings
Adjustable wall support

* refers to hose outlet in models with hose



Hose reel G



DIESEL



FEATURES

	DIESEL <i>without hose</i>	DIESEL <i>with hose Ø20</i>	DIESEL <i>with hose Ø25</i>
Inlet ["]:	1"F	1"F	1"F
Outlet * ["]:	1" M / 1" M	1" M; 3/4"M	1" M
Max pressure [bar]:	10	10	10
Max hose Ø [mm]:	25 ; 20	20	25
Hose fitting:	Ø 25 M; Ø 20 M	Ø 20 M	Ø 25 M
Max hose length [m]:	15; 20	20	15
Tubo included (lunghezza) [m]:	-	20	15
Flow losses [lpm]:	6 @ 70lpm	4 @ 70lpm	4 @ 70lpm
Protection cover:	-	included	included
Hose's auto-stop system:	yes	yes	yes
Allowed fluids:	Diesel	Diesel	Diesel
Forbidden fluids:	gas, alcool, water, gasoline, kerosene	gas, alcool, water, gasoline, kerosene	gas, alcool, water, gasoline, kerosene
Material:	painted steel	painted steel	painted steel
Sealing material:	NBR	NBR	NBR
Fitting material:	nichel plated steel, brass	nichel plated steel, brass	nichel plated steel, brass
Temperature min; max [°C]:	-20/+55	-20/+55	-20/+55
Dimension [mm]:	640x360x700	640x360x700	640x360x700
Weight (without hose) [Kg]:	27.5	27.5	27.5
Weight (with hose) [Kg]:	-	36	37.7

Accessories:

Fittings
Adjustable wall support

* refers to hose outlet in models with hose